

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 12 Page 5059)  
-----  
Set ¼ sec. post, from which  
    A W.Oak, 15" dia., bears N.87°E., 400 lks.  
    A Maple, 6" dia., bears N.20°W., 433 lks.

Douglas Co. Surveyors Office - Milo Godfrey - Oct. 1963 - C.S. File 53/33-26  
-----  
Not found.

Ken Hoffine - For: Lone Rock Timber Co - Feb. 2020 - M176-45  
-----  
Set - 5/8"x40" iron rod with 2.5" aluminum cap mkd: LONE ROCK TIMBER T27S R4W ¼ S27|S28 2019 LS 2291  
    25" Oregon W.Oak bears N.76½°E., 141.6 ft. We scribe T27S R4W S27 ¼ BT & TAG.  
    42" D.Fir bears N.33¾°W., 384.4 ft. we scribe T27S R4W S28 ¼ BT AND TAG.  
    30" Oregon W.Oak bears N.88½°E., 265.7 ft. (Possible record N.87°E., 264 ft) Cut out face and we tag.  
    5/8" iron rod with Yellow plastic cap mkd: LONE ROCK TIMBER LS2291 bears N.0°41'10"E., 425.83 ft. (property corner)  
    5/8" iron rod with Yellow plastic cap mkd: LONE ROCK TIMBER LS2291 bears N.28°38'12"W., 489.82 ft. (property corner)  
Corner lies in open pasture on west facing slope approximately 150 ft North-East of large pond.  
We bury corner 0.5 ft below ground level and place a rock over top of corner.  
We place a 5½ ft. T-Post with metal plate and tag 1.0 ft. North.