



PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

23" Fir now dead, with partially healed double blaze with scribing visible "¼ S15 CS BT" bears S.76°E., 13.0 ft.  
20" Fir now 20" stump 3 ft. high, no blaze visible, bears S.76°W., 18.0 ft.  
19" B.Oak now 22" snag 7 ft. high with scribing visible "¼ S15 CS BT" bears N.44°E., 38.5 ft.  
25" B.Oak now a depression in ground, bears N.23°W., 65.2 ft.  
No evidence of orig. 16" Oak was found.  
New BTs- 6" Madrone bark scribed "¼ S15 CSBT" bears S.69°E., 48.0 ft.  
4" Madrone bark scribed "¼ S16 CSBT" bears S.72½°W., 35.9 ft.  
See C.S. File for sketch and comments.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 9/28/2000 - C.S. File 66/16-48  
-----  
Found - 1958 DCS0 brass cap, iron pipe protrudes 12" above ground.  
10" now 12" dia., 8 ft. high rotted Oak snag, bears N.25°E., 13.0 ft. 0BT  
23 now 22" dia., down & rotted D.Fir root hole bears S.76°E., 13.0 ft. (1958)  
20" now 20" dia., rotted D.fir stump bears S.76°W., 18.0 ft. (1958)  
6" now 10" dia., Madrone with faint low bark scribing "¼ 15 CS BT" we rescribe higher on a single blaze "¼ S15 CS BT" bears S.69°E., 48.0 ft. (1984)  
4" now 11" dia., Madrone, no bark scribing visible we rescribe "¼ S16 CS BT" on a double blaze, bears S.72½°W., 35.9 ft. (1964)  
New - 6" dia., B.Oak double blazed & scribed "X CS BT" bears N.26°E., 14.0 ft. This tree is at a 3way fence corner with fence lines running N-S and East.  
6" dia., Madrone double blazed & scribed "¼ S16 CS BT" bears N.40°W., 28.5 ft.  
No descent trees around corner.