

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>14" dia., Apple single blazed low & scribed "X BT" bears N.16°W., 313.0 ft.</p>
<p>Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 3/12/2008 - C.S. File 67/25-31 ----- Fd. Ok as per DCSO 2000 renewal</p>
<p>BLM resurvey by George M. Winter, Cadastral Surveyors, under Group No. 2704, surveyed July 2013/Feb. 2016 - (DCSO records Vol. 58 page(s) 23351) ----- The standard ¼ sec. cor. of sec. 34 only, perpetuated by Smith, Deputy County Surveyor, in 2000, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly)mkd. and bearing tree mkd. by Smith An apple, 15" dia., bears N.16°E., 313.0 ft., with scribe marks X BT visible on an open blaze. An embedded mound of stone is north alongside the cor. From the corner S., 28 ft., to a two-track road, bears S.44°E. and N.44°W.</p>
<p>2</p>