

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 457100

PRIMARY CORNER DESCRIPTION E 1/16 Cor. N. Line Sec. 3, T28-4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bureau of Land Management Dependent Resurvey - Irving Zirpel Jr. & Wm. Glenn under Special Instructions dated August 29, 1957. (DCSO records, Volume 29 Pages 12223-24)

Point for the E 1/16 sec. cor. of sec. 3 only, on N bdy. of T28S R4W

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

E 1/16
1958

from which

A Fir, 13" dia., bears S.29 3/4°E., 200 lks., mkd: E 1/16 S3 BT.

A Fir, 45" dia., bears S.37°W., 455 lks., mkd: E 1/16 S3 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/17/2000 - C.S. File 66/14-30

Found - 1958 BLM BC/IP in fence line. Fence corner with fence line running south & east bears North 6.5 ft.

13" now 18" dia., D.Fir with a fully healed single blaze bears S.29 3/4°E., 130.9 ft. (rec. S.29 3/4°E., 133.3 ft.) 1958

New - Area around 1958 SW BT bulldozed - no evidence fd.
6" dia., D.Fir double blazed & scribed "E 1/16 S3 CS BT" bears S.83°W., 33.3 ft.

Double trunked D.Fir double blazed & scribed "E 1/16 S3 CS BT" root crown of double trunk bears S.13½°E., 7.5 ft.