TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 12 Page 5053)

Set ¼ sec. post, from which
A Willow 3" dia. bears S.35°W., 24 lks. dist.
A R.Fir 18" dia. bears N.67°E., 60 lks. dist.

Bureau of Land Management Dependent Resurvey by James Jelley under Group No. 700 - Survey April 1970 - (DCSO records, Volume 35 Page 14459)

Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor. Set an Iron post, 28" long 2½" dia. 24" in the ground, with brass cap marked:

¼
S 34 | S 35
T 27 S | R 4 W
1970

from which
A Fir 9" dia. bears N.84 3/4°E., 51 lks. marked ¼ S35 BT.
A Fir 16" dia. bears N.57½°W., 29 lks. marked ¼ S34 BT.

Found ok by Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/10/2000 - C.S. File 66/14-21

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 3/10/2008 - C.S. File 67/25-30

Fd. Ok, 2 live BTs as per 1970 BLM renewal.