TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 12 Page 5053)

Set post cor. to secs. 34, 35, 26 and 27, from which
A Laurel 12" dia. bears N.39°W., 64 lks. dist.
A Laurel 10" dia. bears N.35°E., 33 lks. dist.
A B.Oak 4" dia. bears S.38°W., 59 lks. dist.
A B.Oak 2" dia. bears S.3°E., 72 lks. dist.

Bureau of Land Management Dependent Resurvey by James Jelley Group No. 700 - Survey April, 1970 (DCSO records Volume 35 Pages 14459-60)

Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an Iron post, 28" long 2½" dia. 14" in the ground, to bedrock, mkd. X, and in a mound of stone, 3 ft. base, to top, with brass cap mkd: T 27 S R 4 W

S 27|S 26
S 34|S 35
1970

from which
A Fir 40" dia. bears N.43°E., 25½ lks. dist. marked T27S R4W S26 BT.
A Fir 15" dia. bears S.56½°W., 78½ lks. dist. marked T27S R4W S34 BT.
A Fir 6" dia. bears N.9¾°W., 93½ lks. dist. marked T27S R4W S27 BT.
Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the iron post.

There is no suitable bearing tree available within limits in sec. 35.