

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 12 Page 5054)

-----  
Set ¼ sec. post, from which  
    A Pine 18" dia. bears S.2°W., 36 lks. dist.  
    A R.Fir 28" dia. bears N.88°E., 10 lks. dist.

Milo E. Godfrey, Deputy Co. Surveyor - Stoffel and Stone  
Oct. & Nov. 1963 - C.S. File 53/33-31

-----  
Found - Old, rotted Pine stump, used for fence corner post  
          S.2°W., 23.8 ft., cut open & found old axe  
          marks at top of old rotted face, no scribing  
          found.  
          48" old Fir stump N.88°E., 6.6 ft., very old axe  
          marks visible on bark which is flaking badly.  
          No scribing found in stump, but knowing of Flint's  
          preference for bark scribing, I believe he bark  
          scribed this tree. Found limb or knot which  
          had been broken or chopped off at approx.  
          time of Flint's survey.  
Set brass cap at cor. mkd: County Surveyor's Office, 1963  
  T27S R4W ¼ S27|S26  
New BTs - 24" I.Cedar N.72°W., 103.5 ft. mkd. ¼ S27 CS BT.  
          9" D.Fir S.22°W., 84.2 ft. mkd. ¼ S27 CS BT.  
          No good trees available East of line.  
          A fence corner, fences S. & W., bears South 24 ft.  
          A rock outcrop (12x15x7 ft.) high on S. side bears  
          S.77°W., 34 ft. (SE cor. tied)  
Corner lies approx. 100 ft. south of top of ridge.

Found County brass cap and 4 BTs, BLM Resurvey in 1970 by  
James Jelley- DCSO records, Volume 35 Page 14462.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 2/23/2000 - C.S. File 66/14-35

-----  
Found - 1963 DCSO BC/IP, protrudes 12" above ground.  
          28" now 40" dia., 3½ ft. high D.Fir stump, no marks  
          found, bears N.88°E., 7.5 ft. (rec. N.88°E.,  
          6.6 ft. dist. to trunk) OBT  
          18" now 15" dia., 4 ft. high Pine stump, no marks fd  
          bears S.2°W. 24.5 ft. (rec. S.2°W. 23.8') OBT  
continued next page

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

24" now 27' dia., I.Cedar with a fully healed double blaze, bears N.72°W., 103.5 ft. 1963  
9" now 18" dia., D.Fir with a fully healed double blaze bears S.22°W., 84.2 ft. 1963  
12'x15'x7' boulder south side bears S.77°W., 34 ft. 1963.  
New - We chisel new 5" "+" (on east face of 1963 boulder) "+" bears S.86½°W., 28.1 ft.  
11" dia., I.Cedar double blazed & scribed "¼ S26 CS BT" bears N.75°E., 37.4 ft.