

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 2; 34 & 35 of T26-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
 (DCSO Records, Volume 11 Page 4428)

-----  
 Set post cor. to secs. 34, 35, 2 and 3, from which  
 A mound was thrown up as per instructions, no trees near.

Bureau of Land Management Dependent Resurvey - Glenn S.  
 Baughman, Contract #52500-CT5-1116, Survey Oct/Dec. 1975  
 (DCSO records, Volume 39 Page 15786)

-----  
 Point for corner at proportionate distance, there is no  
 remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia. 22" in the ground, with  
 brass cap mkd: T26 S R  
                   S 34 | S 35 4  
                   S 3 | S 2 W  
                   T27S

- 1975 from which  
 An Oak 12" dia. bears N.18°E., 60 lks. dist. mkd. T26S  
     R4W S35 BT.  
 An Oak 24" dia. bears S.23°E., 23 lks. dist. mkd. T27S  
     R4W S2 BT.  
 An Oak 14" dia. bears S.76°W., 56 lks. dist. mkd. T27S  
     R4W S3 BT.  
 An Oak 14" dia. bears N.82°W., 62 lks. dist. mkd. T26S  
     R4W S34 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
 Stephen J. Flause - 9/26/2000 - C.S. File 66/16-45

- Found - 1975 BLM brass cap/iron pipe, protrudes 8" above  
           ground.  
           12" now down 13" rotted Oak with a partially healed  
           blaze scribing visible "T26S R4W S35 B" root  
           hole bears N.18°E., 29.6 ft. (1975)  
           14" now 14" down burnt Oak, no scribing visible,  
           root hole bears N.82°W., 40.9 ft.  
           14" now 16" dia., W.Oak with a partially healed  
           rotted blaze I rescribe on a single blaze above  
           old blaze "X S3 CS BT" bears S.76°W., 37.0 ft.  
           (1975)  
           24" now 29" dia., W.Oak with a fully healed single  
           blaze bears S.23°E., 15.2 ft. (1975)  
 New - 10" W.Oak, double blazed & scribed "T26S R4W S34 CS  
           BT" bears N.72°W., 37.2 ft.  
           27" B.Oak double blazed & scribed "T26S R4W S34 CS  
           BT" bears N.4½°W., 32.5 ft.