TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION South ¼ corner for Sec. 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records, Volume 12 Page 5045)

Set ¼ sec. post, from which
A R.Fir 10" dia. bears S.20°E., 16 lks. dist.
A R.Fir 10" dia. bears N.45°E., 10 lks. dist.

Remeasurement & Resurvey by Addison R. Flint, Contract #56 dated March 1, 1855 (DCSO records, Volume 12 Page 5048)

Set ¼ sec. post, from which
A Fir 28" dia. bears S.65°E., 25 lks. dist.
A Fir 30" dia. bears N.89°W., 24 lks. dist.

Resurvey of Exteriors, W.H. Byars, under contract #376 dated January 22, 1881 (DCSO records, Volume 12 Page 5081)

Qr. sec. cor., set new post as per instructions, bearing trees all standing, viz: March 9, 1881,
A Fir 28" dia. bears S.65°E., 25 lks. dist.
A Fir 30" dia. bears N.89°W., 24 lks. dist.

Milo Godfrey, Clete Putnam - Douglas Co. Surveyors Office July 3, 1961 - C.S. File 49/130-18

Found - D.Fir now 36" S.56½°E., (not 65°E.), 16.5 ft., old bark scribing "4S B" plainly visible.
D.Fir now 48" N.81°W., not N.89°W., 14.8 ft., no scribing or scars found but believe it to be other original BT.
Set Iron pipe with brass cap mkd: County Surveyors Office 1961
T27S R4W ¼ S 35
New BTs - 7" I.Cedar N.26½°W., 9.8 ft. mkd: ¼ S35 CS BT.
11" D.Fir N.33°E., 25.6 ft. mkd: ¼ S35 CS BT.

Found OK by D.Edwards, 4/2001 - M138-8 & 65/34-6A & B