

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 12 Page 5057)</p> <p>-----</p> <p>Set ¼ sec. post, from which A W.Oak 7" dia. bears N.3°E., 42 lks. dist. A W.Oak 4" dia. bears S.78°E., 56 lks. dist.</p>
<p>Milo E. Godfrey, Deputy Co. Surveyor - Stoffel and Stone January 1964 - C.S. File 53/33-59</p> <p>-----</p> <p>Found - 39" W.Oak N.3°E., 27.7 ft. This tree has been opened many years ago and center portion burned away. (See affidavit of Mr. Lorris Singleton in field notes file)</p> <p>No trace of SE bearing tree.</p> <p>Set brass cap at cor. mkd: County Surveyors T27S R4W ¼ <u>S 2</u> Office, 1964 <u>S 11</u></p> <p>New BTs - 20" W.Oak N.39°E., 102.0 ft. mkd. ¼ S2 CS BT. 17" W.Oak N.51°W., 21.5 ft. mkd. ¼ S2 CS BT. No suitable trees available south of line.</p> <p>A 3-way fence corner, fences E., W., and N. bears N.51°W., 3.7 ft.</p>
<p>Found OK by Roberts, Feb. 1996 - L.P. 1996-0097 A&amp;B</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 9/14/2000 - C.S. File 66/16-38</p> <p>-----</p> <p>Found - 1964 DCSO brass cap iron pipe protrudes 7" above ground. 7" now 39" dia., 35 ft. high W.Oak snag with burnt out center bears N.3°E., 27.7 ft. OBT (Alive) 20" now 21" dia., down W.Oak with a fully healed blaze root hole bears N.39°E., 102.0 ft. 1924 17" now 19" double trunked W.Oak with a fully healed double blaze bears N.51°W., 21.5 ft. to center of southerly scribed trunk.</p> <p>New - 10" dia., D.Fir double blazed &amp; scribed "¼ S2 CS BT" bears N.28°E., 55.6 ft. 25" dia., W.Oak double blazed &amp; scribed "¼ S2 CS BT" bears N.15°W., 66.0 ft. 3-way fence corner E-W &amp; N bears N.45°W., 3 ft. No trees south of corner.</p>