

PRIMARY CORNER DESCRIPTION East ¼ Cor. to Section 26 only

Alias	Description

<p>(Original ¼ cor. for Secs. 25 and 26 set by Addison Flint, Contract #56 in 1855 - See DCSO records, Volume 12 Page 5050)</p>
<p>GLO retracement & resurvey by Elmer F. Strickler, Under Special Instructions dated Jan. 22, 1917 (DCSO records, Volume 12 Page 5085)</p> <p>-----</p> <p>At apportioned distance, set a basalt stone, 15 x 10 x 8", 10" in the ground, for ¼ cor. of sec. 26 only, marked ¼ on W. face, from which</p> <p> A Fir 22" dia. bears S.68°W., 26 lks. marked ¼ S 26 BT.</p> <p> A Fir 14" dia. bears N.45°30'W., 49 lks. marked ¼ S 26 BT.</p>
<p>Milo E. Godfrey, Deputy Co. Surveyor - Stoffel; Stone; Darby and Halterman - Oct. 1963 - C.S. File 53/33-14</p> <p>-----</p> <p>Found - Rock called for in gov't notes "¼" mkd. on W. face. Rotten Fir stump N.45¼°W., 32.3 ft. scribing visible on old face, "¼ S26 BT".</p> <p> Rotten Fir stump S.68°W., 17.2 ft. partial scribing visible "¼".</p> <p>Drove ¾" Iron Rod alongside rock at corner.</p> <p>New BTs- 6" Madrone N.55°W., 31.9 ft. mkd. ¼ S26 CS BT.</p> <p> 4" Madrone N.86°W., 24.2 ft. mkd. ¼ S26 CS BT.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/23/2000 - C.S. File 66/14-36</p> <p>-----</p> <p>Found - Stone top measures 10"x8" protrudes 8" out of ground with ¼ marked on NW face (1917)</p> <p> ¾" iron rod set by DCSO in 1963 along NW side of stone 0.6 ft. Protrudes 5" out of ground.</p> <p> <u>From center top of stone</u></p> <p> 22" now badly rotted D.Fir stump with rotted blaze, no scribing found, bears S.68°W., 17.2 ft. (OBT)</p> <p> 14" now rotted to ground D.Fir bears N.45½°W., 32.3 ft. OBT</p> <p> 6" now 9" dia., Madrone with a fully healed single blaze bears N.55°W., 31.9 ft. 1963</p> <p> 4" now 6" dia., Madrone with a fully healed single blaze bears N.82½°W., 23.0 ft. (Rec. N.86°W., 24.2 ft.) 1963</p> <p> 1917 BLM BC/IP W½ S25 only bears S.2°W., 27.4 ft.</p> <p>New - 16" dia., D.Fir single blazed & scribed "¼ S26 CS BT" bears N.36½°W., 9.6 ft.</p>
<p>continued next page</p>

PRIMARY CORNER DESCRIPTION East ¼ Cor. to Section 26 only

Alias	Description

BLM Dependent resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2189 surveyed June/Sept 2008 - (DCSO records Vol 57 Pgs 22499-500)

The ¼ sec. cor. of sec. 26 only, perpetuated by Godfrey, in 1963, further perpetuated by Smith, in 2000, monumented with a basalt stone, 15x10x8", projecting 8" above the ground, with marks ¼ visible on the W. face (alongside of which is an iron rod, 3/4" dia., firmly set, projecting 8" above the ground), from which the remains of BTs mkd. by Strickler

A sawed fir stump, 27" dia., bears S.68°W., 15.8 ft., with no marks visible. (Record, 17.2 ft.)

A sawed fir stump, 23" dia., bears N.45½°W., 32.3 ft., with no marks visible.

and bearing trees mkd. by Godfrey

A madrone, 6" dia., bears N.86¼°W., 23.3 ft., with a healed blaze.

A madrone, 10" dia., bears N.54°W., 31.7 ft., with a healed blaze.

and bearing tree mkd. by Smith

A fir, 17" dia., bears N.37¾°W., 9.5 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap (properly) mkd.

Bury the basalt stone inverted along the W. side of the stainless steel post and bury the iron rod, 30 ins. long, inside the stainless steel post.