

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec Cor for 23 & 26 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 12 Page 5050)

-----  
Set post, cor. to secs. 23, 24, 25 & 26, from which  
A Laurel 3" dia. bears N.22°E., 11 lks. dist.  
A Laurel 3" dia. bears N.36°W., 5 lks. dist.  
A Laurel 3" dia. bears S.85°E., 5 lks. dist.  
A Laurel 3" dia. bears S.57°W., 25 lks. dist.

GLO Dependent Resurvey - By Elmer F. Strickler, Deputy  
Surveyor under Special Instructions dated Jan. 22, 1917  
(DCSO Records, Volume 12 Page 5084 and 5085)

-----  
Found no trace of the sec. corner. At apportioned distance,  
Set a limestone 14x9x6", 10" in the ground, for cor. of secs.  
23 and 26, marked with 2 notches on S. and 4 notches on N.  
edge; from which  
A Fir 18" dia. bears S.54°30'W., 19 lks. dist. marked  
T 27 S R 4 W S 26 B T.  
A Fir 18" dia. bears N.33°30'W., 24 lks. dist. marked  
T 27 S R 4 W S 23 B T.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A.  
Bilow - December 1958 - C.S. File 49/130-7

-----  
Found - Stone at corner at both BTs as recorded in 1917.  
SW BT, now stump, shows good scribing "T27S R4W".  
NW BT, now down, shows good scar. I do not open.  
Brass cap at record dist. & bearing for section cor  
for  $\frac{24}{25}$  I do not renew this cor. No trees near

New BTs for section corner for  $\frac{23}{26}$  :  
5" Laurel bears S.73°W., 14.6 ft. scribed S26 CS BT.  
15" W.Fir bears N.56°W., 46.0 ft. scribed S23 T27S R4W  
CS BT.  
42" Cedar bears S.71°W., 97.5 ft. scribed S26 T27S R4W  
CS BT.  
I set  $\frac{3}{4}$ " Iron rod alongside stone at corner.

BLM Dependent Resurvey, Glenn Baughman - Under Contract  
#52500-CT5-1116 - Survey Oct/Dec. 1975 - (DCSO records, Vol  
39 Pages 15787-88)

-----  
The cor. of secs. 23 and 26 only, monumented with a  
limestone, 14 x 9 x 6", firmly set 10" in the ground, mkd.  
with 2 notches on S. and 4 notches on N. edges, (cont)

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec Cor for 23 & 26 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

subsequently perpetuated and recorded by James Byron in 1959, with a  $\frac{3}{4}$ " Iron rod, firmly set protruding 6" above ground alongside, from which the remains of the bearing trees mkd. by Strickler:  
A root hole bears N.33 $\frac{1}{2}$ °W., 24 lks. dist. with a down fir alongside 24" dia. with illegible scribe marks visible on opened blaze.  
and trees mkd. by Byron  
A Madrone 10" dia. bears S.73°W., 22 lks. dist. with healed blaze.  
A Fir 26" dia. bears N.56°W., 70 lks. dist. with healed blaze.  
A Cedar 44" dia. bears S.71°W., 148 lks. dist., with scribe marks T27S R4W S26 BT visible on open blaze. At the corner point, set an ironpost 28" long 2 $\frac{1}{2}$ " dia. 23" in the ground with brass cap mkd: T 27 S R 4 W  
$$\begin{array}{r} S 23 \\ S 26 \\ \hline 1975 \end{array}$$
  
Deposit corner stone and reset iron rod alongside iron post. Corner is located at fence corner, wire fences extend S. & W.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/23/2000 - C.S. File 66/14-34  
-----  
Found ok - SW 42" Cedar from 1958, now solid stump 1 scribe on sawn face "X BT"  
No measurements made at corner.

DCSO-GIS Corner visitation - 3/8/2006 - Typed: 1/27/2011 - C.S. File 67/33-1  
-----  
Monument - GLO/BLM 3" BC/IP  
Comment - OK

BLM Dependent resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2189 surveyed June/Sept 2008 - (DCSO records Vol. 57 Page 22501)  
-----  
The cor. of secs. 23 & 26 only, bears N.3°21'42"E., 48.38 ft., monumented with an iron post, 2 $\frac{1}{2}$ " dia., firmly set, projecting 6" above the ground (buried alongside of which is the orig. stone, 14x9x6", with no marks visible), with brass cap (properly) mkd. from which the remains of a bearing tree mkd. by Strickler, reported by Baughman  
  
continued next page

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23 & 26 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A roothole bears N.33½°W., 15.8 ft., alongside of which is a fir trunk, 16" dia., with fragmentary scribe marks visible on an open blaze.  
and the remains of bearing trees mkd. by Byron, in 1958  
A sawed cedar stump, 44" dia., bears S.71°W., 97.7 ft., with scribe marks X BT visible on an open blaze.  
A madrone, 11" dia., bears S.73°W., 14.5 ft., with a healed double blaze.  
A fir, 36" dia., bears N.56°W., 46.2 ft., with a healed blaze.