TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 600439

PRIMARY CORNER DESCRIPTION West ¼ Corner Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 12 Page 5051)

Set ¼ sec. post, from which
A W.Oak 20" dia. bears S.28°W., 33 lks. dist.
A W.Oak 22" dia. bears N.27°E., 24 lks. dist.

G.L.O. resurvey by Elmer F. Strickler, Deputy Surveyor under Special Instructions dated Jan. 22, 1917 (DSCO records, Volume 12 Pages 5088-9)

After careful and diligent search, am unable to find any trace of old ¼ cor. Set an iron post, 3 ft. long, 1" dia. 26" in the ground, for ¼ cor. of sec. 13 only, with brass cap marked:

¼
S 13
1917

from which
A W.Oak 10" dia. bears N.68°E., 68 lks. dist. marked ¼ S 13 BT.
A Fir 9" dia. bears S.78°30'E., 181 lks. dist. marked ¼ S 13 BT.

James W. Byron, Deputy County Surveyor - Milo Godfrey; S.A. Bilow - December 31, 1958 - C.S. File 49/130-8

Found - Brass cap at corner.
9" now 24" Fir stump (Rec. S.78½°E., 119.4 ft.) should be S.77°E., 119.4 ft. good scribing visible.
10" now 18" W.Oak shows good scar. I do not open. (Rec. N.68°E., 44.8 ft.) should be N.68°E., 48.6 ft.
New BT - 10" B.Oak bears S.36°E., 29.0 ft. scribed ¼ S13 CSBT

Found OK, Burton Holt, March 1982 - M 91-37

Fd. & used BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1925, surveyed June/Dec. 2000 - (DCSO rec. Vol. 53 Page(s) 20547)