

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 5051)

Set Post, cor. to secs. 11, 12, 13 & 14, from which
A B.Oak 15" dia. bears S.73°E., 341 lks. dist.
A B.Oak 15" dia. bears N.47°E., 82 lks. dist.
A B.Oak 10" dia. bears N.81°W., 14 lks. dist.
A B.Oak 12" dia. bears S.57°W., 32 lks. dist.

GLO resurvey and retracement by Elmer F. Strickler, Under
Special Instructions dated Jan. 22, 1917 - (DCSO records,
Volume 12 Pages 5089-90)

Intersect the cor. of secs. 11, 12, 13 and 14, which is an
old decayed post, marked and witnesses as described by the
surveyor general. Alongside the old corner,
set an Iron post, 3 ft. long, 2" dia. 24" in the ground, for
cor. of secs. 11, 12, 13 and 14, with brass cap marked

T27SR4W
S11|S12

S14|S13

1917

from which

A B.Oak 15" dia. bears N.47°E., 82 lks. dist. marked
T 27 S R 4 W S 12 B T. (Orig. BT)

A Fir 16" dia. bears S.65°E., 442 lks. dist. marked
T 27 S R 4 W S 13 B T (New BT)

A B.Oak 16" dia. bears N.81°W., 14 lks. dist. marked
T 27 S R 4 W S 11 B T (Orig. BT)

No other tree available; raise a mound of stone 2 ft.
base 1½ ft. high, W. of cor.

This corner is 100 ft. above the draw.

Milo E. Godfrey, Deputy Co. Surveyor - Stoffel and Stone
October 1963 - C.S. File 53/33-19

Found - Iron pipe with brass cap set in 1917 in E. & W.
fence line.

Stump hole only N.47°E., 82 links.

Stump hole only N.81°W., 14 lks.

No trace of Fir BT to SE.

Did not find mound of stone.

New BTs - 17" W.Oak S.5½°W., 231.4 ft. mkd. T27S R4W S14 CSBT

12" W.oak N.83°W., 100.0 ft. mkd. T27S R4W S11 CSBT

Power pole with transformer, mkd: "Copco B10111" bears
N.4½°E., 194.7 ft.

(Corner found OK, November 1990, M 111-24)

CONT.

