

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION South ¼ Corner for Sec. 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, Contract #44 dated May 30, 1854
(DCSO records, Volume 12 Page 5045)

Set ¼ sec. post, from which
 A R.Fir 30" dia. bears N.3°W., 13 lks. dist.
 A R.Fir 24" dia. bears S.3°E., 13 lks. dist.

Remeasurement and survey, by Addison R. Flint, Contract #56
dated March 1, 1855 (DCSO records, Volume 12 Page 5048)

Set ¼ sec. post, from which
 A Laurel 14" dia. bears N.3°W., 13 lks. dist.
 A Cedar 8" dia. bears S.35°W., 35 lks. dist.

Exteriors by W.H. Byars, Contract #376 dated January 22, 1881
(DCSO records, Volume 12 Page 5081)

Orig. sec. cor., set new post as per instructions, bearing
trees all standing viz:
 A Laurel 14" dia. bears N.3°W., 13 lks. dist.
 A Cedar 8" dia. bears S.35°W., 35 lks. dist.

Douglas Co. Surveyors Office - James Byron; M. Godfrey; C.
Putnam - July 13, 1961 - C.S. File 49/130-19

Found - Orig. 8" now 16" Cedar snag S.35°W., 23.1 ft. We
 open & find good scribing on old chip "¼ S".
 No trace of Orig. NW BT found.
Set brass cap at corner & under 36" log, mkd: South ¼ S36
T27S R4W, County Surveyor's Office, 1961.
New BTs - 10" Cedar bears N.9°W., 9.7 ft. scribed S ¼ S36
 CS BT.
 12" Cedar bears N.59½°E., 49.0 ft. scribed S ¼ S36
 CS BT.

David Edwards - For: Seneca Jones Timber Co. - 7/2010 - C.S.
File 65/69-46

Found - DCS Brass cap (In good condition)
 24" Cedar w/healed blaze brs. N.59½°E., 49.0'
New BT - Scribed "T27S R4W S36 BT" bears N.23°E., 38.2'.
Set - 6 ft. steel post 2' East.