



TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION N 1/4 Cor Sec 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2189 surveyed June/Sept 2008 - (DCSO records Vol. 57 Pgs 22497-8)

-----

The ¼ sec. cor. of sec. 36 only, perpetuated by Godfrey, in 1963, further perpetuated by Hostetter, in 2007, monumented with an iron post, 1¼" dia., firmly set, projecting 11" above the ground, with brass cap (properly) mkd.

from which the remains of a bearing tree mkd. by Strickler

A sawed cedar stump, 47" dia., bears S.35°W., 14.5 ft., with a healed blaze.

and the remains of a bearing tree mkd. by Godfrey

A decayed hemlock stump, 28" dia., bears N.48¾°E., 40.8 ft., with a healed blaze.

and bearing trees mkd. by Hostetter

A hemlock, 16" dia., bears N.29¼°E., 25.6 ft., with scribe marks S36 ¼ BT visible on an open blaze.

A fir, 13" dia., bears N.85°E., 8.9 ft., with scribe marks S36 ¼ BT visible on an open blaze.