

TOWNSHIP 27 RANGE 4 POINT IDENTIFIER # 640440

PRIMARY CORNER DESCRIPTION Center 1/4 Sec. 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1925, surveyed June/Dec. 2000 - (DCSO rec. Vol. 53 Page(s) 20551)

Point for the center ¼ sec. cor. of sec. 13, at the intersection with the E. & W. centerline, falls in middle of dirt road.

Drive an iron rod, 36" long, 5/8" dia., 40" in the ground, buried 4" below road surface, with 2" dia. aluminum cap mkd.

T 27 S R 4 W
C 1/4
+
S 13
2000

from which

A stainless steel post, 28" long, 2½" dia., set 24" in the ground for a reference monument, bears N.66°54'47"E., 29.89 ft., with brass cap mkd. RM T27S R4W C 1/4 S13 29.89 FT TO COR 2000 and an arrow pointing to the corner.

A fir, 16" dia., bears S.78 3/4°W., 15.9 ft., mkd. C ¼4 S13 BT.

A fir, 11" dia., bears N.7°W., 14.1 ft., mkd. C ¼ S13 BT.

Each new bearing tree has a 2½" X ¼" magnetic nail (MAG-NAIL) driven at the base on the right side-center, unless otherwise described in the corner description