

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 642200

PRIMARY CORNER DESCRIPTION South ¼ Cor. for Sec. 25 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

(Original Corner for Secs. 25 and 36 set by Flint in 1855  
See DCSO records, Volume 12 Page 5049)

GLO resurvey and retracement by Elmer F. Strickler under  
Special Instructions dated Jan. 22, 1917 (DSCO records,  
Volume 12 Page 5082)

-----  
Set a yew post, 3 ft. long 4" sq., 24" in the ground, for ¼  
cor. of sec. 25 only, marked ¼ S 25 on N. face; from which  
A Yew 5" dia. bears N.67°W., 17 lks. marked ¼ S 25 BT.  
A Fir 24" dia. bears N.38°E., 47 lks. marked ¼ S 25 BT.

Milo E. Godfrey, Deputy Co. Surveyor - Stoffel; Darby; Stone  
Halterman - Oct. 1963 - C.S. File 53/33-12

-----  
Found - Fir, uprooted and slid short dist. downhill,  
N.38°E., 31.0 ft., cut open and found good  
scribing "¼B".  
7" Yew N.67°W., 11.2 ft. Found old blaze, but face  
had rotted before being covered by overgrowth.  
No scribing on rotted face.  
Set brass cap at cor. mkd: County Surveyor's Office, 1963  
T27S R4W ¼ S 25  
Blaze & rescribe 7" Yew N.67°W., 11.2 ft. mkd: ¼ S25 CS BT.  
New BT - 21" Hemlock N.16°W., 70.2 ft. mkd: ¼ S25 CS BT.  
Corner is under a log approx. 30" diam.

Tony Hostetter - For: Seneca Jones Timber Co. Co. - June 2007  
- M153-40

-----  
Found - 1963 Douglas Co. Surveyor brass cap (C.S. 53/33)  
12" yew, scribing visible, BLM tag, bears N.67°W.,  
11.2 ft.  
New BT - 12" Hemlock, scribed "S25 ¼ BT", bears N.22°E., 7.2  
ft. to spike.  
28" Fir, scribed "S25 ¼ BT", bears S.65°W., 12.6 ft.  
to spike.

BLM Dependent resurvey by A Bert Skeesick, Cadastral Surveyor  
and Robert H. Browning, Survey Tech, under Group No. 2189  
surveyed June/Sept 2008 - (DCSO records Vol. 57 Page 22497)

-----  
The ¼ sec. cor. of sec. 25 only, perpetuated by Godfrey, in  
1963, further perpetuated by Hostetter, in 2007, monumented  
with an iron post, 1¼" dia., firmly set, projecting 10" above  
the ground, with brass cap (properly) mkd.

continued next page

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 642200

PRIMARY CORNER DESCRIPTION South ¼ Cor. for Sec. 25 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of bearing trees mkd. by Strickler  
A roothole bears N.27¼°E., 41.9 ft., alongside of which is  
the fir trunk, 25" dia., with a healed blaze. (Record,  
N.38°E., 31.0 ft.)  
A yew, 10" dia., bears N.67°W., 11.2 ft., with fragmentary  
scribe marks visible on an open blaze.  
and the remains of bearing trees mkd. by Hostetter  
A hemlock, 10" dia., bears N.23°E., 8.0 ft., with scribe  
marks S25 ¼ BT visible on an open blaze.  
A sawed fir stump, size indeterminate, bears S.68°W., 14.0  
ft with scribe marks S25 ¼ BT visible on an open blaze.

2