

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & S. 31, T27-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 12 Page 4967)

-----  
Set ¼ sec. post, from which  
A cedar, 6" dia., bears S.5°W., 8 lks.  
A cedar, 6" dia., bears N.4°E., 7 lks.

Douglas Co. Surveyors Office - Milo Godfrey - April 1964 -  
C.S. File 53/33-68

-----  
Not found.

BLM resurvey by Boyd W. Peterson, under Group #1480, Surveyed  
July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18831-32)

-----  
Point for the ¼ sec. cor. of secs. 31 and 36, at  
proportionate distance; there is no remaining evidence of the  
original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22  
ins. in the ground, with brass cap mkd.

T 27 S

¼  
R 4 W | R 3 W  
S 36 | S 31

1989

from which

A fir, 4 ins. diam., bears S. 31° E., 12½ lks. dist.,  
mkd X BT.

A fir, 6 ins. diam., bears N. 87° W., 26 lks. dist.,  
mkd. ¼ S36 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the  
stainless steel post.