

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

(Original ¼ corner for 13 & 18 set by Addison Flint, Contract #56 in 1855 - See DCSO records, Volume 12 Page 4968)

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1925, surveyed July/Dec. 2000 - (DCSO rec. Vol. 53 Page(s) 20526)

Point for the ¼ sec. cor. of sec. 13 only, T. 27 S., R. 4 W., at proportionate distance.

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.

T 27 S
R 4 W R 3 W
1/4|
S 13|
2000

from which

A cedar, 21" dia. bears S.76¼°W., 49.4 ft. , mkd. ¼ S13 BT

A fir, 9" dia. bears N.16 ¾°W., 16.2 ft. , mkd. ¼ S13 BT

Each new bearing tree has a 2½" X ¼" magnetic nail (MAG-NAIL) driven at the base on the right side-center, unless otherwise described in the corner description.

Deposit a magnet in a white plastic case at the base of the stainless steel post.