

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
 (DCSO Records, Volume 12 Page 4968)

-----  
 Set post cor. to secs. 12, 13, 7 and 18, from which  
     A Laurel 4" dia. bears N.53°W., 9 lks. dist.  
     A Laurel 5" dia. bears N.85°E., 27 lks. dist.  
     A Laurel 3" dia. bears S.15°E., 9 lks. dist.  
     A Laurel 3" dia. bears S.10°W., 23 lks. dist.

Resurvey of Portion E. Bdy of T27-4 by Elmer F. Strickler  
 under Contract #36 dated March 14, 1917 and Special  
 Instructions dated Jan.22, 1917 (DCSO records, Volume 12  
 Page 5034)

-----  
 At Apportioned distance, Set an iron post, 3 ft. long, 2"  
 dia., 24" in the ground, for cor. of secs. 7, 12, 13, and 18,  
 with brass cap marked:

T27S	
R4W	R3W
S 12	S7
S 13	S18
1917	

from which

A Fir 40" dia. bears N.17°E., 17 lks. dist. mkd. T27S  
     R3W S7 BT.  
 A Fir 8" dia. bears S.16°45'E., 61 lks. dist. marked T27S  
     R3W S18 BT.  
 A Fir 30" dia. bears S.58°W., 43 lks. dist. marked T27S  
     R4W S13 BT.  
 A Fir 12" dia. bears N.54°W., 46 lks. dist. marked T27S  
     R4W S12 BT.

This corner is on a spur sloping NE.

Milo Godfrey, Doug. Co. Surveyor, etal - October 1963 - C.S.  
 File 53/33-22

-----  
 Found - I. Pipe with brass cap set in 1917, in mound of large  
           rocks.  
           44" Fir N.17°E., 11.2 ft., shows very plain axe  
           scar, tree alive.  
           48" Fir S.58°W., 28.4 ft., shows very plain axe scar  
           tree alive.  
           Fir stump S.16¼°E., 40.3 ft., scar visible.  
           23" Fir N.54°W., 29.5 ft. (Rec. 30.4 ft.) scar not  
           visible. Reblaze and rescribe this tree, (in  
           wood) "T27S R4W S12 CS BT" New BT - 10" D. Fir  
           S.41°E., 34.0 ft. mkd: T27S R3W S18 CSBT

continued next page

PRIMARY CORNER DESCRIPTION Sec. cor. 12 & 13; 7 & 18 of T27-3


Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Found and tied in 1958 BLM resurvey, DCSO records, Volume 29  
 Page 12408)

Found OK, Burton Holt, March 1982, M 91-37  
 Found OK, DCSO, Oct. 31, 1989, C.S. File 64/3-1

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under  
 Group #1925, surveyed July/Dec. 2000 - (DCSO rec. Vol. 53  
 Page(s) 20526-7)

-----  
 (Condition report)  
 The cor. of secs. 7, 12, 13, & 18, perpetuated by Godfrey,  
 Douglas County Deputy Surveyor, in 1963, monumented with an  
 iron post, 2" dia., firmly set, projecting 12" above ground,  
 along the E. side of which is a mound of stone, 4 ft. dia.,  
 1 ft. high, with brass cap mkd.



from which the remains of the bearing trees mkd. by Strickler  
 A fir, 43" dia., bears N.17°E., 11.2 ft., with a healed  
 blaze.

A sawed stump, 12" dia., bears S.25°E., 40.3 ft., with a  
 healed blaze. (Record, S.16°45'E.)

A fir, 46" dia., bears S.58°W., 30.0 ft., with a healed  
 blaze. (Record, 28.4 ft.)

A fir, 26" dia., bears N.54°W., 30.4 ft., with a healed  
 blaze.

and bearing tree mkd. by Godfrey

A fir, 43" dia., bears S.41°E., 34.0 ft., with a healed  
 blaze.

Corner lies 2 ft. N. of end post of a barbed wire fence which  
 extends North.

From this cor., the Bureau of Land Management Geodetic  
 Control Station No. EC 41301 at latitude 43°13'10.992"N.,  
 longitude 123°06'37.843"W. (NAD 1983 (91)), determined by  
 the NAVSTAR Global Positioning System, bears  
 S.7°34'44"W., 3031.55 ft. (mean bearing and sea level  
 distance), monumented with an aluminum cap, 3¼" dia., firmly  
 set, flush with the ground, mkd. EC 41301 GPS 2000.

continued next page

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. cor. 12 & 13; 7 & 18 of T27-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Retracement & rehabilitation by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2300 surveyed March 2008 - (DCSO records 2009 BLM Plat & Vol. 56 Page 21838)

-----

The cor. of secs. 7, 12, 13, & 18 on East bdy of the TP monumented with an iron post, 2" dia., firmly set, projecting 11" above the ground with brass cap (properly) mkd from which the remaining BTs mkd. by Strickler, reported by Skeesick

A fir, 43" dia., bears N.17°E., 11.2 ft. with a healed blaze.

A fir, 47" dia., bears S.58°W., 30.0 ft. with a healed blaze.

A fir, 28" dia., bears N.54°W., 30.4 ft. with a healed blaze.

and BT mkd. by Godfrey, reported by Skeesick

A fir, 20" dia., bears S.41°E., 34.0 ft. with a healed blaze. (Rec. 43" dia.)

The geodetic position shown hereon was determined by a tie utilizing dual frequency carrier phase GPS receivers relative to the National Spatial Reference System. (NAD 1983 (COR96))  
Latitude: 43°13'40.68"N                      Longitude: 123°06'32.46"W