

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 040030

PRIMARY CORNER DESCRIPTION S.W. Cor. Stevens DLC #40

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Addison R. Flint, Contract #28, dated July 1854 ----- To S W Cor C 40, Set Post, from which B.Oak, 18" dia. bears N.20°E., 146 lks. Raised mound with trench as per instructions.</p>
<p>N. E. Richardson; Hamilton Estate - 1950 - C.S. 44/3B, M8-62 ----- Computed S.20°W. from old stump, probable BT in traces of old fence line. Set - 1" pipe with brass cap mkd: County Surveyors Office S. W. D.L.C. 40 24" B.Oak, S.56°15'W., 13.0 ft. blazed & scribed SW Cl. 40 CS BT. 18" B.Oak, S.66°15'E. 16.4 ft. blazed & scribed SW Cl. 40 CS BT.</p>
<p>Doug. Co. Surveyors office, Larry E. Monrean - P.L. Earle October 31, 1978 - C.S. 60/17-19 ----- Found - Orig. post with raised mound & trench <u>not found</u>. 1950 DCSO brass cap found. B Oak, 24" now 36" bears S.56¼°W., 13.0 ft. Tree has well healed single blaze. B.Oak, 18" now 24" bears S.66¼°E., 15.8 ft. to center of base, 16.4 ft. to center of trunk (Rec. 16.4 ft.) Tree has well healed single blaze. Orig. B. Oak not found. Tagged found bearing trees.</p>
<p>Doug. County Surveyors Office - Randall Smith, Deputy - Stephen Flause - May 3, 1993 - C.S. File 64/43-17 ----- Found - 1950 DCSO 2½" dia. brass cap on a 1½" O.D. I.Pipe protrudes 8" above ground. (Note: lines on brass cap marked as if SE Cor.) 24" now 40" dia. B.Oak with a fully healed blaze bears S.56¼°W., 13.0ft. (agrees w/rec. 1950) 18" now 26" dia. B.Oak with a fully healed blaze bears S.66¼°E., 15.8 ft. (agrees w/1978 ren.) New BTs- 6" dia. W.Oak double blazed and scribed "SW DLC 40 CS BT" bears S.31°E., 31.5 ft. 9" dia. W.Oak double blazed and scribed "SW DLC 40 CS BT" bears S.34°W., 38.0 ft.</p>
<p>Fd. Ok by K. DeGroot, Oct. 1994 - M 121-14 Fd. OK by K. DeGroot, July 1998 - LP 1999-0065 Fd. Ok by M. Heimburger, 7/2016 - M171-13</p>