

PRIMARY CORNER DESCRIPTION NW Cor. Barker DLC #43

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated July, 1854

To N.W. Cor. C 43. Set post from which
A B.Oak 14" dia. bears S.68°E., 130 lks. dist.
Raised mound with trench as per instructions.

James W. Byron, Co. Surveyor - W. Penley & Jack Heritage
April 16, 1971 - C.S. 53/38-21

Found - Orig. 10" now 36" down & partly rotted Oak,
S.68°E., 85.8 ft. We open & find good re-
verse scribing "C T R 5 W" & other scribe
marks.

Set - Brass cap at cor. mkd. County Surveyors T27S R5W
Office, 1971 N.W. Cor. DLC #43

New BTs - 18" B.Oak bears N.89°E., 62.7 ft. scribed NW DLC
43 CS BT.

30" B.Oak bears N.45°W., 89.4 ft. scribed NW DLC
43 CS BT.

Note - Corner 8 ft. south of E-W fence.
Position of cor. checks call at "Leave Valley, begin ascent".

Doug. County Surveyors Office - Randall Smith; Stephen Flauser
April 27, 1993 - C.S. File 64/43-18

Found - 1971 2½" dia. DCSO brass cap on a 1½" O.D. I.P. pro-
trudes 13" above ground.

Orig. 14" B.Oak now depression in ground, no remains
visible, near bearing and dist. of orig. rec.
(S.68°E., 85.8 ft.) Orig. BT position.

18" now 18" dia., down Oak with a fully healed
double blaze, root hole bears N.89°E., 62.7 ft.
(agrees w/rec.) 1971 BT.

30" now 31" dia. B.Oak with a fully healed single
blaze, bears N.45°W., 89.4 ft. (agrees w/rec.)
1971 BT.

New Accessories:

8" dia. W.Oak double blazed and scribed "NW DLC 43
CS BT" bears N.88½°E., 110.5 ft.

2' x 2' exposed portion of rock outcrop, a 4"
chiseled "+" on easterly face, + bears
S.16½°W., 91.0 ft.

53" dia. ponderosa Pine double blazed & scribed "NW
DLC 43 CS BT" bears S.31°W., 300.0 ft.

New BTs and + out side DLC lines. No reasonable trees or B.O.s
inside DLC.