

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Tsp. Cor. Rges 5 & 6 (SW Cor. Sec. 31)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile - April 7, 1853

-----  
Set - Post to Secs. 36 and 31 from which  
A W. Oak, 20" dia. bears N.22¼°E., 441 lks.  
A W. Oak, 20" dia. bears N.50½°W., 352 lks.

Arthur Boyer; Claude Crocker; J.H. Wolford; B.A. Lane  
1934-37-38 - Volume 4 Pages 50-58

-----  
Set corner from old BTs.  
Set - ¾" x 36" round bolt for corner from which:  
New BTs - White Oak, 12" dia. bears N.22°W., 58.5 ft.  
White Oak, 14" dia. bears N.81°30'E., 20 ft.

Douglas Co. Surveyors Office - Randall Smith; Stephen Flause  
September 21, 1989 - C.S. 64/1-4

-----  
Found - ¾" dia. iron bolt protruding 6" above ground bolt  
leans 4" west of plumb.  
Orig. 20" W. Oak now 41" dia. B. Oak with a fully  
healed single blaze, tree is rotted in center  
on NW side shows evidence of previous axe work  
bears N.24½°E., 295.7 ft. (Rec. N.22¼°E.,  
291.1 ft.) Note: tree is over a rise and not  
visible from corner.  
Orig. 20" now 40" dia. 8 ft. high rotted oak snag  
with a previously opened blaze, reverse  
scribing visible "T S" bears N.50½°W., 232.2'.  
12" now 12" dia. W. Oak with a fully healed double  
blaze bears N.22°W., 58.5 ft.  
14" now 18" dia. W. Oak with a fully healed double  
blaze bears N.84°E., 20.6 ft. (Rec. N.81½°E.,  
20.0 ft.)  
Set - A 2 3/8" dia. DCS0 brass cap on a 1 3/8" x 32" long  
iron pipe is set at referenced plumb position  
of ¾" iron bolt. DCS0 BC/IP protrudes 7"  
above ground and mkd. Douglas County Surveyors  
T27S

R6W R5W  
S 36 | S31  
-----  
T28S R6W  
S 1 1989

3/4" dia. iron bolt measures 30" long is set along north side  
of DCS0 BC/IP, protrudes 5" above ground.  
New BT - 7" dia. W. Oak double blazed and scribed "T27S R5W  
S31 CS BT" bears N.1½°E., 27.7 ft.

cont.

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Tsp. Cor. Rges 5 & 6 (SW Cor. Sec. 31)

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

DCS0-GIS Corner visitation - 4/15/2004 - Typed: 1/28/2011 -  
C.S. File 67/33-1

-----  
Monument - BC/IP 1.25"  
Comment - OK

Fd. DCS0 Brass Cap 7/2022 J. Estabrook - 2022-0035