

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 100417

PRIMARY CORNER DESCRIPTION Meander Cor. between Secs. 18 & 13

Alias 835130 Description M.C.

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Over So.Umpqua River by triangulation to (left ?) bank between
Secs. 18 and 13 - and

Set - Meander Post from which
A G. Oak, 30" dia. bears N.25°E., 108 lks. dist.
A Double Oak, 42" dia. bears N.22½°W., 137
lks.dist.

Bank on North side low and overflows by a common stage of
water and densely covered with brush.

On P.E.R.A. Project - Ben B. Irving - Frank Cain; B.A. Lane
N.E. Richardson - Vol. 4 Pgs. 50-58 - 1935

All indication of corner gone.

Set - 5/8" x 42½" iron rod by proportional measurement,
4.8 ft. south of the south rail S.P.R.R.
A channel iron 1¼" x 18", 14" in ground under right
of way fence.
A bridge bears N.16°30'W., 62 ft. about 455 ft. from
B.C. R.R. curve left north of cut on R.R.
A W. Oak 14" dia. bears S.60°30'W., 117.4 ft. mkd.
M.P. C.S. B.T.

Douglas County Surveyors Office - John M. Powell; Frank Jones;
Terry Connell - Aug. 22, 1966 - C.S. 53/38-10

Found - No trace of 1¼" iron, N.16°E., 62.0 ft. under
fence.

3/8" I.R. with small 3 cornered flange for M.C.
14" W. Oak, now 17" S.60½°W., 117.4 ft. opened
for scribe "S" (bearing tree OK, tagged with
yellow tag.

Iron rod is now 7.0 ft. due south and 10.3 ft. due west of
south rail of R.R. track. Also, yellow location tags on
R.R. tie. Telephone pole #4 N.71°E., 31.3 ft.

Douglas County Surveyors Office - R.W. Smith; S.J. Flause
August 27, 1987 - C.S. 62/45-15

Found - A 5/8" iron rod with a 3-cornered flange that has
a small prong protruding on each corner. I.R.
is set in R.R. grade along south side of
tracks 3" below gravel surface (CONT NEXT PG)

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 100417

PRIMARY CORNER DESCRIPTION M.C. between secs. 18 & 13, Right bank

Alias 835130 Description M.C.
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

CONT. - - with flange and prongs up, noted as a 3/8" I.R.
in 1966. (Rec. from Vol. 4 Pg. 54)
A 14" now a 19" W.Oak with a previously opened fully
healed single blaze, bears S.63°W., 117.4 ft.
Rec. S.60½°W., 117.4 ft.
Telephone pole #4 bears N.69°W., 31.0 ft. (Rec. N.71°W
31.3 ft.)
Not found -A channel iron from 1935. Yellow location tag set
on R.R. tie is gone.
Found - Iron rod is located due south 7.7 ft. (Rec. 7.0) &
due west 10.3 ft of south R.R. track.
New Accessory: A BT tag with PK nail on R.R. tie bears
N.39°E., 5.0 ft.
Note: Corner lies in R.R. grade approx. northwesterly
of rock cutbank.