

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & S. 1, T. 27-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set 1/4 Sec. post, from which  
    A G. Oak, 12" dia. bears N.64°E., 45 lks. dist.  
    A G. Oak, 11" dia. bears S.62°W., 18 lks. dist.

Ben B. Irving; N. E. Richardson; Ernest Brown  
1934 - Volume 4 Pages 50-58

-----  
Set by proportional measurement drove 1" x 24" machine gun barrel 23" in ground and set a yellow pine stake 3" sq. x 36" long with R.5W. on East face, ¼ S. on north face; R.6W. on West face; C.S.T.27S. on South face; from which  
    W. Oak, 14" dia. bears S.68°45'E., 59.5 ft. mkd. ¼ S.  
        6 C.S. B.T.  
    W. Oak, 20" dia. bears S.83°10'W., 77.7 mkd. ¼ S. 1  
        C.S. B.T.

Doug. Co. Surveyors Office - James W. Byron; M. Godfrey;  
S. Bilow - Jan. 16, 1958 - C.S. 49/62-1

-----  
Found - Machine gun barrel at corner.  
    W. Oak, 20" dia., S.83°W., 77.7 ft. showing good scars. Did not chop open.  
No trace of S.E. tree marked by Irving in 1934 could be fd.  
New BT - Blaze & scribe a 6" madrone, N.60°E., 29.7 ft.  
    "¼ S6 CS BT".  
Did not set new corner. Barrel in good condition.

Found OK - Nov. 1980 - B. Shaner, R.M. 3 - 38

Doug. County Surveyors Office - Randall W. Smith, Stephen J. Flause - Mar. 18, 1993 - C.S. File 64/41-8

-----  
Found - 1" O.D. gun barrel protruding 3" above ground (1934 B.B.I. renewal)  
Accessories Found -  
    20" now 22" dia. W.Oak with a fully healed blaze, bears S.83¼°W., 77.7' (agrees with rec.) 1934 B.B.I. ren.

CONTINUED ON NEXT PAGE

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. 6; Sec. 1 T. 27-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

6" now 9" dia. Madrone with a fully healed blaze, bears N.60°E., 29.7'. (agrees with rec.) 1958 J. Byron renewal.

Set - 2 3/8" brass cap on a 1 3/8" O.D. x 32" long iron pipe is set at referenced position of gun barrel and protrudes 6" above ground. 1" O.D. x 24" long gun barrel is set along north edge of BC/IP protruding 2" above ground.

New Accessories -

- 9" Madrone double blazed and scribed "¼S1 CS BT" bears S.30°W., 9.4'.
- 9" B.Oak double blazed and scribed "¼S6 CS BT" bears S.66°E., 33.3'.