

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Elder & Gile - Contract #31, dated April, 1853</p> <p>-----</p> <p>Set - ¼ Sec. post, (on top of ridge) from which A W. Oak, 16" dia. bears N.27°E., 36 lks. dist. A W. Oak, 14" dia. bears N.19½°W., 81 lks. dist.</p>
<p>On S.E.R.A. Project - Claude Crocker; J.H. Wolford; B.A. Lane; Arthur Boyer - Vol. 4 Pgs. 50-58 - 1934-37-38</p> <p>-----</p> <p>Set from original bearing trees by driving 3/4" x 36" round iron bolt for corner. Marked new bearing trees as follows: Forked Fir 14" dia. bears N.56°E., 18.6 ft. White Oak 16" dia. bears N.52°W., 20.5 ft.</p>
<p>Douglas County Surveyors Office - James Byron & crew November 1961 - C.S. 49/64-38</p> <p>-----</p> <p>Found - 3/4" iron bolt at corner. NW BT shows good scars. I do not open. NE BT, now dead, 18" Fir. We open & find good scribing.</p> <p>New BT - 8" W.Oak bears N.38°E., 16.2 ft. scribed S¼ S31 CS BT.</p>
<p>Found OK by H. Pieske June, 1982, M 90 - 22 and Found OK August, 1990, M 112 - 12</p>
<p>Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 4/22/2008 - C.S. File 67/25-42</p> <p>-----</p> <p>Fd. Iron bolt & 2 live BTs</p>
<p>Fd. 3/4" iron bolt 7/2022 J. Estabrook - 2022-0035</p>