

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Elder & Gile, Contract #31 dated April, 1853 ----- Set ¼ Sec. post, from which A W.Oak, 32" dia. bears N.27 ¾°E., 140 lks. dist. A W.Oak, 8" dia. bears S.65 ¾°E., 180 lks. dist.</p>
<p>James W. Byron; M. Godfrey - June 14, 1957 - C.S. 47/200 ----- Found - Orig. SE BT (now 30" W.Oak. I open & find good scribing "BT". Also find parts of rotted oak stump that checks for bearing & dist. to N.E. BT. Set - Brass cap at corner mkd. County Surveyor's Office 1957 ¼S <u>19</u> T27S, R5W. 30 Note: Corner is 5.5 ft. south of east-west fence line. Blaze & Scribe: 12" W.Oak S.55°W., 47.4 ft. ¼ S30 CSBT. 10" W.Oak N.28½°E., 29.1 ft. ¼ S19 CSBT.</p>
<p>Douglas Co. Surveyors Office - Karen Reed; Terrie Plouff May, 1980 - C.S. 60/34 61/6-43 (corrected 5/20/2020) ----- Found - 1" I.P. with BC properly mkd. protruding 1.1 ft. above ground. An orig. 8" dia. W.Oak now 31" with previously chopped open blaze visible scribe "BT" bears S.65 ¾°E., 118.8 ft. A 12" dia. W.Oak now 13" with well healed double blaze bears S.55°W., 47.4 ft. A 10" dia. W.Oak now 11" with well healed double blaze bears N.28½°E., 29.1 ft. New BT - An 18" dia. W.Oak scribed "¼ S19 CS BT" in a double blaze bears N.71°W., 51.7 ft. Note - Corner lies approx. 5.5 ft. south of down E-W fence.</p>
<p>Fd. BC & 3BTs Fd. by Herm Pieske 2/2006 - Vol. 22 Pg. 20D N 571568.68 E 1244450.79 <u>OCS 27</u></p>
<p> </p>