TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 141100

PRIMARY CORNER DESCRIPTION ¼ Cor. N. side S. 6, T28-5

Alias Description
Alias Description
Alias Description
Alias Description

Original - Elder & Gile, Contract #31, dated April 1853

Set - 1/4 Sec. post from which
A W. Oak, 16" dia. bears S.28°W., 80 lks. dist.
A W. Oak 16" dia. bears S.35°E., 184 lks. dist.

On S.E.R.A. Project - Claude Crocker; J.F. Wolford; B.A. Lane; Arthur Boyer - Vol. 4 Pgs. 50-58 - 1934-37-38

Set corner from one original BT by driving 3/4" x 36" round iron bolt in ground. Marked new bearing trees as follows:
Fir, 14" dia. bears S.22°15'E., 120.3 ft.
White Oak, 8" dia. bears S.46°45'W., 17.3 ft.

Found OK, H. Pieske, June 1982, M 90-22
Found Bolt August, 1990, M 112 - 12

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 4/22/2008 - C.S. File 67/25-42

Fd. Iron bolt, W.Oak BT ok, Fir BT is tall stump.