

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set Post From which

A Fir, 12" dia. bears N.12°W., 24 lks. dist.

A Y. Oak, 8" dia. bears N.41°E., 90 lks. dist.

On S.E.R.A. Project - Claude Crocker; J.F. Wolford; B.A. Lane; Arthur Boyer; Robt. Boyer - Vol. 4 Pgs. 50-58  
1934-37-38  
-----

Found - One original BT almost gone from which corner was set. A stake, from which:

New BTs - Pine 24" dia. bears S.36°45'W., 18.0 ft.

Fir, 12" dia. bears S.54°E., 22.0 ft.

Douglas County Surveyors Office - John M. Powell and Crew  
March, 1966 - C.S. 53/38-24  
-----

Found - 24" Pine, now 34", S36°45'W., 18.0 ft. Shows good scar. No trace of corner stake by Boyer.

Set - Brass Cap at ¼ cor. mkd.: County Surveyors Office  
1966 T27S R5W ¼ S31/S32

All BTs in good condition including:

12" D. fir now 19" S.54°E., 22.0 ft. shows good scar.

This corner lies on top of ridge, running E. and W.

Found OK by H. Pieske, June 1982 - M 90 - 22 and  
August, 1990, M 112 - 12