

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor for 5, 6, 7 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31, dated April, 1853

-----  
Set post cor. to Secs. 5, 6, 7 and 8, from which  
A Y.Oak, 12" dia. bears N.11¼°W., 78 lks. dist.  
A Y.Oak, 10" dia. bears N.53°E., 73. lks. dist.  
A Y.Oak, 18" dia. bears S.60°W., 68 lks. dist.  
A W.Oak, 10" dia. bears S.82½°E., 236 lks. dist.

Douglas Co. Surveyors Office, L.E. Monrean; K. Reed; M.S. Means - December 20, 1979 - C.S. 60/34-31

-----  
Found - An Orig. Y.Oak, 10" now an 18", 20 ft. snag bears N.53°E., 48.2 ft. We open this tree to find scribe "5W 27S" reverse scribing "R5W T27S B" and notch.  
An orig. 18" Y.Oak, now a 22", 12 ft. high rotted snag, bears S.53½°W., 44.9 ft. (Record S.60°W) We partially open blaze to find scribing "BT" and "axe notch".  
An orig. 12" Oak now a rotted & down tip out, size indeterminate bears N.11¼°W. 51.5 ft to root hole  
An orig. 10" W.Oak, now a 22" bears S.85½°E., 159.1 ft (Rec. S.82½°E. 155.8 ft) We do not open tree  
Set - A 1" x 36" I.P. with brass cap stamped "Douglas County Surveyors T27S R5W S6 S5 S7 S8 1979", at position from orig. BTs.  
New BTs - A 10" B.Oak 15" at base, (two trunk tree) scribed "T27S R5W S7 CS BT" in a double blaze bears S.84°W., 7.3 ft. dist.  
An 8" B.Oak scribed "T27S R5W S6 CS BT" bears N.23°W 16.8 ft.  
A 12" P.Pine scribed "T27S R5W S5 CS BT" bears N.9½°E., 67.8 ft.

Found OK, June 1993 by B.Rogers - M117-33.  
Found OK, Oct. 1997 by D.Edwards - M 127-63  
Found OK by M. Heimburger, April 2003 - M137-59 A&B  
Fd. Ok, by R. Quimby 5/2007 - M153-30

Fd. Ok by Heimburger 9/2008, M157-3A&B. This corner was used to proportion the corners 240600;300500;300600 these corners were calculated but not set on this survey.