TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 203100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, T28-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to secs. 5 and 6, from which
A Fir, 16" dia. bears S.1°W., 16 lks. dist.
A Fir, 16" dia. bears S.65½°E., 56 lks. dist.

A. Boyer; N.E. Richadson - Nov. 20, 1937 (Record Source not found. "old" cor. book, Page 106)

Found original BTs in good shape. Marked B.T. on bark.
Drove ¾" x 36" round iron bolt for corner, from which
36" Fir bears S.65°30'E., 56 lks. Orig. BT.
16" Fir bears S.1°W., 16 lks. Orig. BT.

James W.Byron Crew - November 1961 - C.S. 49/64-53

Found - Iron bolt & both BTs which show good scars.
Set - Brass cap alongside I. Bolt mkd. County Surveyors Office 1961

S6|S5 T28S R5W

Found OK by H. Pieske, June 1982, M 90 - 22

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 4/22/2008 - C.S. File 67/25-42

Fd. bolt, 1 live OBT, 1 snag.