TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 5; & S. 32, T26-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
A W.Oak, 6" dia. bears N.55°W., 42 lks.
A Y.Oak, 24" dia. bears S.3°E., 146 lks.

James W. Byron, D. McFarland - March 23, 1962 - C.S. 49/125-10

Found - Both orig. BTs.:
6" now 12" W.Oak, N.55°W., 27.7 ft. previously opened, shows good scribing "¼".
24" now 30" B.Oak, snag S.7°E., not S.3°E., 92.4 ft. not 96.4 ft., shows good scribing.

Fence Corner thus:

```
                x
                | ↙ 4.0 ft.
     --x--x---- ○  ¼ cor.      ⇑
                |
                x
```

Set - Brass cap at ¼ cor. mkd. ¼ S 32 / S 5 T26S R5W T27S
County Surveyor's Office, 1962.

New BTs - Rescribe orig. now 12" W.Oak N.55°W., 27.7 ft. "CS BT"
7" W.Oak ~~S.18°W~~., S.19°W., (per research 6/30/2022) 21.4 ft. scribed ¼ S5 CS BT.

Found OK per B.Rogers, May 1987, M 104 - 40
Found OK, Steven Ness, Nov. 1991, M 114 - 59

Fd. Ok by Heimburger 9/2008, M157-3A&B. This corner was used to proportion the corners 240600;300500;300600 these corners were calculated but not set on this survey.