

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----  
Set post cor. to Secs. 20, 21, 28 & 29, from which  
A W. Oak, 12" dia. bears N.84°E., 10 lks. dist.  
A Y.Oak 13" dia. bears S.20°E., 25 lks. dist.  
A Y.Oak, 15" dia. bears S.63°W., 17 lks. dist.  
A W.Oak, 15" dia. bears N.13°W., 68 lks. dist.

---

James W. Byron, Deputy - Milo Godfrey; C. Putnam - July 2, 1959 - C.S. 49/62-6  
-----  
Found - Orig. 12" now 26" W.Oak N.84°E., 6.6 ft., I open and find good scribing "21".  
Orig. 15" now 30" W.Oak N.13°W., 44.9 ft. shows good scar, I open center, rotted, no scribing found.  
Stump holes that check for SE & SW BTs.  
Set - Brass cap at cor. mkd. County Surveyors Office 1959  

S 20	S 21
S 29	S 28

T27S R5W  
New BTs- 7" W.Oak bears N.24°W., 20.2 ft. scribed S20  
T27S R5W CS BT.  
24" B.Oak bears S.37°W., 14.8 ft. scribed S29  
T27S R5W CS BT.  
6" W.Oak bears S.41°E., 14.9 ft. scribed S28 CSBT  
8" W.Oak bears N.28°E., 27.6 ft. scribed S21  
T27S R5W CS BT.

---

Found OK, April 22, 1980 & May 21, 1984, R. Thompson, M96-58  
Found OK by J. Estabrook, Jan. 2003, 2003-0017 A&B

---

Jerry Estabrook - Crew: Bruce Webster & Ryan Palmer - 2/14/2003 - C.S. File 65/45-15A&B  
-----  
Found - No monument found.  
24" B.Oak, with healed face bears, S.37°W., 14.3 ft. (14.8)  
8" W.Oak, with healed face bears, N.24°W., 20.0 ft. (20.2)  
9" W.Oak, with healed face bears, N.28°E., 27.4 ft. (27.6)  
25" W.Oak, with chopped hole in face area, measured below twin 14" stems bears N.90°E., (N.84°E.) 6.6 ft.  
8" W.Oak, with healed face, bears S.41°E., 14.7 ft. (14.9)  
Set - 2½" brass cap on 1½"x30" iron pipe 0.5 above grade, mkd:  
continued next page

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>T27S R5W S 20   S 21 S 29   S 28 2003 LS 2703</p> <p>Using a best fit from fd. BTs. The B.Oak has a tag that showed distance as 14.3 against rec. (14.8). Using 14.3 seemed to make the remaining BTs a best fit.</p>
<p>Fd. Ok by Herm Pieske, 12/2005 - M149-68 N 571242.19      E 1252393.96      (OCS 27)</p>
<p>Fd. Ok by Heimburger 9/2008, M157-3A&amp;B. This corner was used to proportion the corners 240600;300500;300600 these corners were calculated but not set on this survey.</p>