

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor to Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original- Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A Y.Oak 16" dia. bears N.55°E., 55 lks. dist.
 A Y. Oak 14" dia. bears S.22¾°E., 89 lks. dist.

Douglas Co. Surveyors Office - John M. Powell; Frank Jones;
Joe Brady - March, 1966 - C.S. 53/38-28

Found - Scribed stake at ¼ Cor. mkd. "¼".
 Orig. 16" B.O. now 24" N.55°W., 36.3 ft. Opened tree
 fd. bees, but could feel reverse scribing.
 14" B.O. S22¾°E., 58.7 ft. is gone.
Set - Brass cap at ¼ cor. mkd. County Surveyors Office
 1966, T27S R5W ¼ S4 S9.
New BTs - 9" B.Oak N.50°W., 9.0 ft. scribed ¼ S4 CS BT.
 20" D.Fir S.56°W., 38.0 ft. scribed ¼ S9 CS BT.
Note - This corner is in small draw, 2.6 ft. south of an
 E-W. fence.

Found OK by M. Heimburger, April 2003 - M137-59 A&B

Fd. Ok by Heimburger 9/2008, M157-3A&B. This corner was used
to proportion the corners 240600;300500;300600 these corners
were calculated but not set on this survey.