

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only (south)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 33 & 34, from which
A Y.Oak, 10" dia. bears N.51°E., 64 lks. dist.
A Y.Oak, 9" dia. bears S.63¼°W., 154 lks. dist.

James W. Byron crew - November 3, 1961 - C.S. 49/64-30

Found - Orig. 10" now 30" B.Oak, N.51°E., 42.2 ft. shows
good scar. I do not open.
Pipe at section corner 4|3 & both BTs recorded by
Frear

33|34 50' (W. 48.2' Rec)
 | 4|3
 x

Set - Brass cap mkd. County Surveyors S33|S34 T27S R5W
Office, 1961 T28S
New BT - 16" R.Fir bears N.39°W., 8.0 ft. scribed S33
T27S R5W CS BT.

Randall Smith; Stephen J. Flause - April 22, 1993 - C.S. File
64/43-22

Found - 2½" 1961 brass cap on a 1¼" O.D. I.P., protruding
18" above ground.
10" now 27" dia. B.Oak with a fully healed single
blaze bears N.49°E., 41.5 ft. (Rec. N.51°E.,
42.2 ft.) Orig. BT.
16" now 20" dia., D.Fir with a fully healed double
blaze, bears N.42°W., 8.0 ft. (Rec. N.39°W.,
8.0 ft.) 1961 BT.
1" O.D. Iron pipe protruding 6" above ground, (NW
Cor. Sec. 3, T28S R5W) bears East 48.2 ft.
(agrees w/orig. rec.)
New BT - 18" dia. Madrone bark scribed, "T27S R5W S34 CS BT"
bears N.31°E., 39.3 ft.