

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 & 34 (WC)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, contract #31 dated April, 1853

Set $\frac{1}{4}$ sec. post, from which
 A W.Oak, 9" dia. bears N.20°W., 50 lks. dist.
 A W.Oak, 12" dia. bears N.24°E., 155 lks. dist.

Doug. Co. Surveyors Office - L.E. Monrean, Deputy
P.L. Earle - August 23, 1976 - C.S. 59/18-20

Found - A W.Oak, 12" now 20" bears N.24°E., 102.3 ft. (at
 mag. dec. of 12°E) Tree bears N.33°E., 102.3'
 (20°E Mag. Dec.) Tree has been opened, has
 old blaze with scribe "B" & partial T.
 A B.Oak at approx. position of orig. W.Oak BT. Tree
 bears N.12°W., 31.0 ft. Tree being used as
 fence corner. I opened & found old axe marks,
 no scribing found, possible face rotted. Tree
 has a 20" diameter.

As corner falls in road, I SET a witness corner North 15.0
ft. of true corner position.

Set - Brass cap at witness corner stamped:
 "County Surveyors Office"
 T 27 S R 5 W
 W. C.
 South 15 ft. to $\frac{1}{4}$
 S 33 | S34
 1976

New BTs - A W.Oak 9" bears N.38°E., 52.6 ft. Tree double
 blazed & scribed "WC $\frac{1}{4}$ S34 CS BT"
 A Cedar, 12" bears N.72°W., 56.6 ft. Tree double
 blazed & scribed "WC $\frac{1}{4}$ S33 CS BT".