

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set ¼ Sec. post, from which  
A Y.Oak, 10" dia. bears S.36°E., 37 lks. dist.  
A Y.Oak, 12" dia. bears S.42°W., 72 lks. dist.

Glenn S. Baughman - For: 4 Star Land & Dev. Co.  
Dec. 30, 1967 (Filed March 18, 1968) M 35 - 54  
-----

Set - Brass cap & stamped ¼ Cor. Sec. 9 & 10, T27S R5W  
Scribed - 12" Madrona bears S.4°W., 18.8 ft. scribed ¼ Cor.  
9 & 10, T27S R5W  
6" Oak bears N.76°W., 17.6 ft. scribed ¼ Cor. 9 &  
10, T27S R5W.

Doug. County Surveyors Office - Randall W. Smith, Stephen J.  
Flause - Mar. 22, 1993 - C.S. File 64/41-14  
-----

Found - A 2½" dia. brass cap on an 1½" O.D. iron pipe,  
protruding 13" above ground. (1967 Baughman  
renewal)  
12" now 14" dia. Madrone with a partially healed  
single blaze, illegible scribe marks visible,  
bears S.1½°W., 19.3'. (rec. S.4°W., 18.8', brg  
hits cnt. of trunk, blaze high) 1967 Baughman  
renewal  
6" now 8" dia. B.Oak with a fully healed single  
blaze, bears N.76°W., 17.6' (agrees with rec.)  
1967 Baughman renewal.  
New - 8" dia. D.Fir double blazed and scribed "¼ S10 CS  
BT" bears N.81½°E., 12.4'  
23" dia. Pine double blazed and scribed "¼ S9 CS BT"  
bears S.84°W., 23.0'.  
Note - Corner is 15' south of an E - W running fence.

Found OK by M. Heimburger, April 2003 - M137-59 A&B

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -  
4/21/2008 - C.S. File 67/25-42  
-----

FD. BC & 4 live BTs