

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original -Elder & Gile, Contract #31 dated April, 1853 ----- Set Post Cor. to Secs. 3, 4, 9 and 10, from which A Y.Oak, 24" dia. bears S.17½°E., 187 lks. dist. A W.Oak, 9" dia. bears S.23½°W., 140 lks. dist. A Y.Oak, 10" dia. bears N.78½°E., 240 lks. dist. A Laurel, 11" dia. bears N.77 3/4°W., 234 lks. dist.</p>
<p>A. Boyer, Doug. Co. Surveyor - Wit. Darley Ware; Gordon Ware June 8, 1944 - C.S. 33/23 ----- Found all O.B.T.s except one in Section 3. Set - Oak Post for corner. New BT - Black Oak, 8" dia. bears N.7°E., 79 lks.</p>
<p>Doug. Co. Surveyors Off. - John M. Powell; Frank Jones; Joe Brady - March, 1966 - C.S. 53/38-23 ----- Found - 24" B.Oak, down, S.17½°W., 123.4 ft. Tree had been opened, (orig. BT), scribe visible "S". Orig. 11" Laurel, now 20", N.77 3/4°W., 156.4 ft. no scar visible. Orig. 9" W.Oak, now 19", S.23½°W., 92.4 ft., not much scar for face. 8" B.Oak now , N.7°E., 52.1 ft. opened for scribe "3". (found bearing to be N.15°E.) Set - Brass cap at cor. mkd. County Surveyors Office 1966 T 27 S R 5 W S 4 S 3 S 9 S 10 New BTs - 9" W. Oak N.62°W., 45.2 ft. scribed T27S R5W S4 CSBT 11" W.Oak S.56°E., 17.9 ft scribed T27S R5W S10 CSBT (This tree is corner post for fence cor. N-S.) 5" B.Oak, S.87°W., 50.5 ft. scribed S 9 CS BT.</p>
<p>Doug. County Surveyors Office - Randall W. Smith, Stephen J. Flause - Mar. 22, 1993 - C.S. File 64/41-9 ----- Found as recorded in 1966 DCSO renewal.</p>
<p> </p>