

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 & 4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Elder & Gile, contract #31 dated April, 1853

-----  
Set 1/4 Sec. Post, from which  
    A Laurel, 8" dia. bears S.17 1/2°E., 64 lks.  
    A Y. Oak, 8" dia. bears S.81°W., 92 lks.

A. Boyer - Darley Ware; Gordon Ware - June 8, 1944 -  
C.S.33/23

-----  
Set - Oak post for corner from original bearing tree  
      to SW.  
New BT - Fir 12" dia. bears N.80°E., 212 lks.

Doug. Co. Surveyors Office - Vernon R. Tracy; Jack Heritage  
V. Perron - Feb. 11, 1970 - C.S. 53/38-30

-----  
Found - Orig. 8" now 16" Oak, S.81 1/2°W., 60.7 ft. Down,  
          only axe marks found, badly burned.  
No trace of orig. SE BT. We find Boyer's 1944 BT.  
12" now 16" Fir, N.80°E., 13.9 ft. (Rec. 139.9')  
      alive, previously opened & shows "1/4 S3 CS"  
      scribe. Ring count 26 years.  
Ridge top to South would fit call dist. of 95 lks.  
      good from this location. If we use Boyer's  
      record dist., ridge would be approx. 4 chs.  
      South.

Set - Brass cap mkd: County Surveyors T27S R5W  
  Office 1970 1/4 S 4|S 3

Note: Brass cap lies 2 ft. East of N-S fence.

New BTs - 9" D. fir S.38°E., 19.9 ft. mkd. 1/4 S3 CS BT.  
          18" B.Oak S.19°W., 54.4 ft. mkd. 1/4 S4 CS BT.

Rescribe -Boyers's 16" D. fir N.80°E., 13.9 ft. mkd. 1/4 S3  
          CS BT.

Found ok by K.DeGroot - 6/1998 - 1998-0071