

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records Vol. 12 Page(s) 5117)

Set ¼ sec. post, from which
A W.Oak, 10" dia., bears N.84½°W., 712 lks.
A Y.Oak, 10" dia., bears S.36°E., 104 lks.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Jan. 1994 - C.S. File 64/50-23

Looked for, not found.

Kris DeGroot - For: Dave Hatfield - June 2009 - 2009-0034A-B

Set - 5/8" x 30" iron rod, 4 ft. S. of E-W fence line in creek bottom, 22" in ground to solid rock with a 2" aluminum cap stamped:

T27S R5W

¼

S34|S35

PLS 1941 2009

from which new bearing trees:

A 23" W.Oak bears S.31°15'E., 74.4 ft. Scribed "¼ S35 BT".

A 16" W.Oak bears S.40°15'W., 6.4 ft. Scribed "¼ S34 BT".

New - A 5/8" iron rod bears N.59°39'26"E., 28.16 ft.

A 5/8" iron rod bears N.6°46'24"W., 24.37 ft.