

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set Post cor. to Secs. 10, 11, 14 and 15, from which
A Y.Oak, 9" dia. bears N.54°E., 19 lks. dist.
A Y.Oak, 10" dia. bears N.68½°W., 33 lks. dist.
A Y.Oak, 9" dia. bears S.63°E., 52 lks. dist.
A Laurel, 16" dia. bears S.25°W., 70 lks. dist.

Glenn S. Baughman - For: 4 Star Land & Development Co.
Dec. 30, 1967 (Filed March 18, 1968) M 35 - 54

Set - Brass cap & stamped Sec. cor. 10, 11, 14 & 15,
T27S. R5W.
Scribed - 24" Oak bears S.89°30'E., 16.8 ft.
34" Oak bears S.43°30'E., 40.9 ft.
22" Oak bears S.39°W., 51.8 ft.
14" Fir bears N.43°W., 31.5 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 3/7/94 - C.S. File 64/50-12

Found - 2½" dia., brass cap on a 1½" O.D. I.P. protruding
14" above ground. (1967)
Orig. BTs - looked for, not found.
24" now 24" dia., B.Oak with a fully healed single
blaze bears S.89½°E., 17.7' (Rec. S.89½°E.,
16.8' dist. to face)
34" now 31" dia., B.Oak with a partially healed
single blaze no scribing visible, this is a
high blaze 4½' above ground, bears S.46½°E.,
40.9'. (Rec. S.43½°E., 40.9')
22" now 22" dia., B.Oak with a partially healed
single blaze, illegible scribing visible, bears
S.39°W., 52.4' (Rec. S.39°W., 51.8')
14" now 22" dia., D.Fir with a fully healed single
blaze, bears N.43°W., 36.5' (Rec. N.43°W.,
31.5')

Note - Corner lies at the intersection of a Southerly and
Easterly running fence lines. See sketch in file.

Found OK by DeGroot, April 1999 - M131-34
Fd. OK by K. DeGroot, 5/2008 - 2008-0065