

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A Y.Oak, 10" dia. bears N.27°W., 33 lks. dist.
 A Y.Oak, 11" dia. bears S.59°E., 35 lks. dist.

Glenn S. Baughman - For: 4 Star Land & Development Co.
Dec. 30, 1967 (filed March 18, 1968) M 35 - 54

Set - Brass cap & stamped ¼ Cor. Sec. 10 & 11, T27S R5W
Scribed - 10" Oak bears ~~N.55°E., 74.1 ft.~~REVISED 5/19/80
 N.64°E., 56.1 ft.
 6" Madrona bears ~~N.27°W., 34.7 ft.~~REVISED 5/19/80
 N.58°W., 29.4 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/7/94 - C.S. File 64/50-14

Found - A 2½" dia., brass cap on a 1¼" O.D. iron pipe
 protrudes 9" above ground. 1967
 6" now 12" dia., dead Madrone with a previously
 opened blaze, scribing appears to have been
 axed out, bears N.58°W., 28.8 (Rec. N.58°W.,
 29.4' dist. possible slope measurement) 1967
 10" now 13" dia., W.Oak with a fully healed double
 blaze bears N.64°E. 56.1' (Agrees w/record) 1967
New BTs - 9" dia., Madrone double blazed & scribed "¼ S10 CS
 BT" bears N.54½°W., 104.1'.
 13" dia., double trunked Madrone double blazed and
 scribed "¼ S10 CS BT" on NE trunk bears
 S.13°W., 81.6' to center of NE trunk.
 8" dia., D.Fir double blazed and scribed "¼ S11 CS
 BT", bears S.1½°E., 61.1'.
 See sketch in file.
Note - Corner lies in an East-West fence line. 45' north
 of an east west ravine and 60' southwest of
 the end of a dirt road.

Fd. BC by M Heimburger, 8/2018 - M174-57