

PRIMARY CORNER DESCRIPTION Sec. Cor for 2, 3, 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post corner to Secs. 2, 3, 10 and 11, from which  
A W.Oak, 7" dia. bears N.41°E., 78 lks. dist.  
A Y.Oak, 14" dia. bears N.38½°W., 60 lks. dist.  
A W.Oak, 6" dia. bears S.82°W., 49 lks. dist.  
A Y.Oak, 11" dia. bears S.35°E., 137 lks. dist.

-----  
Glenn S. Baughman - For: 4 Star Land Development Co.  
Dec. 30, 1967 (filed March 18, 1968) M 35 54

-----  
Set - Brass cap stamped Sec. Cor. 2, 3, 10 & 11, T27S R5W  
Scribed - 14" Oak bears N.59°W., 13.4 ft.  
22" Oak bears N.52°E., 43.3 ft.  
12" Oak bears S.67°W., 34.0 ft.  
6" Oak bears S.71°E., 88.0 ft.

-----  
Douglas Co. Surveyors Office - Randall Smith, Stephen Flause;  
April 20, 1994 - C.S. File 64/51-10

-----  
Found -  
2½" dia. Brass Cap on a 1½" O.D. iron pipe, protrudes 12"  
above ground.

Accessories Found -  
14" now 14" dia. W.Oak with a fully healed single blaze,  
bears N.31°W., 12.4 ft. (Rec. N.59°W., 13.4 ft. 1967)  
22" now 26" dia. W.Oak with a fully healed single blaze  
bears N.54 ¾°E., 41.7 ft. (Rec. N.52°E., 43.3 ft.,  
possible slope dist. 1967)  
12" now 16" dia. W.Oak with a fully healed single blaze,  
bears S.67°W., 34.0 ft. (agrees with rec. 1967 BT)  
6" now 8" dia. W.Oak with a fully healed single blaze,  
bears S.71°E., 84.3 ft. (rec. S.71°E., 88.0 ft. 1967)  
BT is in a cluster of W.Oaks, bearing and dist. taken  
to center of scribed trunk.

Note - Corner is approx. 125 ft. east of a four way fence  
corner and 1 ft. south of E-W fence on a westerly  
sloping hill side.  
- Original line notes denote magnetic variances in lines  
leaving section corner.  
- Our bearings taken away from fence line to minimize  
fence line attraction.  
- Original BT's looked for, none found.