

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853  
-----  
Set ¼ Sec. post, from which  
A Y.Oak, 11" dia. bears N.44¾°W., 300 lks. dist.  
A Y.Oak, 10" dia. bears S.16¾°W., 545 lks. dist.

---

Glenn S. Baughman - For: 4 Star Land & Development Co. - Dec. 30, 1967 (filed March 18, 1968) M 35 - 54  
-----  
Set - Brass cap stamped ¼ Cor. Secs. 11 & 14, T27S R5W  
Scribed - 16" Elm bears S.49°W., 165.9 ft.  
8" Oak bears N.5°W., 157.4 ft.

---

Found OK by R. Ware, Feb. 1984 - M 96 - 9

---

Douglas Co. Surveyors Office - Randall W. Smith, Stephen J. Flause - May 26, 1994 - C.S. File 64/51-7

---

No Monument found.  
Accessories Found -  
11" now 28" dia. 15 ft. high dead Oak snag. We open and find good scribing, a partial "BT". bears N.44¾°W., 198.0 ft. (held at orig. rec.) original BT.  
16" Elm, now 23" dia. Ash with a partially healed single blaze, good illegible scribe marks visible, bears S.49¾°W., 163.8 ft. (rec. S.49°W., 165.9 ft. to a 1967 proportioned position) 1967 BT.  
No evidence of original SW BT found.  
No evidence of 1967 NW BT found.  
Bearings taken from a position determined from one orig. BT.  
Set - 2 3/8" dia. brass cap on a 1 3/8" O.D. by 32" long iron pipe is set at record bearing and distance from remaining original bearing tree. BC/IP protrudes 2" above ground. Brass Cap marked:  
DOUGLAS COUNTY SURVEYORS  
T27S  
1 S11 R  
4 S14 5  
1994 W  
OFFICE

---

New - 16" dia. W.Oak double blazed and scribed "¼ S14 CS BT" bears S.14¾°W., 247.1 ft.  
25" Maple double blazed and scribed "¼ S11 CS BT" bears N.34½°W., 184.0 ft.  
25" dia. B.Oak double blazed and scribed "¼ S11 CS BT" bears N.64½°E., 253.6 ft.  
Note - Corner lies approx 30 ft. northeast of pond dike toe, in wet marshy area.