

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A Fir, 6" dia. bears S.32¼°E., 18 lks. dist.
 A Laurel, 10" dia. bears N.47°E., 71 lks. dist.

Glenn S. Baughman - For: 4 Star Land Development Co.
Dec. 30, 1967 (filed March 18, 1968) M 35 - 54

Set - Brass cap stamped ¼ Cor. Secs. 2 & 1, T27S R5W
Scribed - 4" Madrona bears N.20°W., 57.0 ft. scribed ¼
 Cor. Sec. 2, T27S R5W
Set - 1" I. Rod bears S.14°E., 44.0 ft.

Douglas Co. Surveyor's Office - Randall Smith; Stephen Flauser
CS 64/52-2 - 6/22/94

Found - 2½" dia. Brass cap on a 1½" O.D. Iron pipe
 protruding 17" above ground. BC/IP leans 7" N.E.
 of plumb (1967).

 T27S R5W
 2|11
 LS536 1968

Accessories FD. -

 1" Iron rod protruding 3" above ground, bears
 S.18½°E. 40.8' (rec S.14°E. 44') 1967
 4" Madrone BT from 1967 renewal now gone

New Monuments -

 BC/IP is plumbed and referenced, measures 36" long.
 BC/IP returned to plumb position, protrudes 8" above
 ground.

New Accessories -

 14" dia., Madrone double blazed & scribed "¼ S2 CS
 BT", bears N.80 ¾°E. 146'.
 5/8" by 32" long I.R. with Alum DCSO cap stamped
 "B01 1994" protrudes 6" above ground, bears
 S.85°W. 10'.
 5/8" by 32" long I.R. with Alum DCSO cap stamped
 "B02 1994", protrudes 6" above ground, bears
 N.45°W. 25'.

Found OK by N. Hibbs, Aug. 2001 - M137-25

