TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 2; & S.35, T26-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
A Y.Oak, 24" dia. bears N.48°W., 132 lks. dist.
A W.Oak, 18" dia. bears S.81°W., 487 lks. dist.

Milo E. Godfrey & Crew - March 31, 1964 - C.S. 49/125-100

Found - Stump of W.Oak, S.81°W., 321.4 ft., now 24", opened & fd. good scribing.
48" B.Oak, N.48°W., 87.1 ft. Faint scar visible. Did not open.

Set - Brass cap at cor. mkd. County Surveyors Office, 1964 T26S ¼ S35/S 2 T27S R5W

New BTs - 9" W.Oak, S.20°W., 58.0 ft. mkd. ¼ S2 CS BT.
12" W.Oak, N.79°W., 85.6 ft. mkd. ¼ S35 CS BT.

Note - Bearings not true for this corner, read with compass set for Var. 19° 30' E.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - 6/22/94 - CS 64/52-4

Found - 2½" Brass cap on 1½" O.D. Iron Pipe protruding 16" above ground (1964) COUNTY SURVEYORS OFFICE
T 26 S
¼ S 35/S 2 R 5
T 27 S W
1964

BTs - Orig SW BT Now Gone
24" Now 48"dia., B. Oak with a possible scar, bears N.61°W. 87.1' (rec. N.48°W. 87.1') OBT
9" now 14" dia., W. Oak with a fully healed double blaze, bears S.20°W. 58' (agrees with rec) 1964
12" now 13" dia., W. Oak with a fully haled double blaze, bears N.79°W. 85.6' (agrees with rec)

New Accessories -
17" dia., W. Oak double blazed and scribed "¼S2 CS BT", bears S.5°W. 104.7'.