

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs - A 6" W. Oak bears N.72°E., 18.4 ft. scribed "¼ S36 CS BT"
An 8" W. Oak bears N.18½°W., 18.9 ft. scribed "¼ S 35 CS BT"
This corner lies beneath a high voltage electrical transmission line.

Doug. County Surveyors Office - Randall W. Smith & Stephen J. Flause. April 22, 1993. - C.S. File 64/43-4

Found - 2" brass cap on a 1" O.D. iron pipe, flush with ground (1974 DCS0)
Truck spring found flush with ground along south edge of BC/IP. (1948 Frear)
½" I.D. iron pipe found along east edge of BC/IP protruding 15" above ground (probably set as a locator for corner monuments by sources unknown)
Large B.Oak multi trunk clump, with a rotted stump of indeterminable size at center, no blazes or scribing visible, bears N.87½°E., 81.0 ft. (rec. East, 81.0 ft.) 1948 Frear.
6" now 8" dia. W.Oak with a fully healed double blaze, bears N.72°E., 18.4 ft. (agrees with rec.) 1974 DCS0.
8" now 10" dia. W.Oak with a fully healed double blaze, bears N.20 ¾°W., 18.9 ft. (rec. N.18½°W 18.9 ft.) 1974 DCS0.
1¼" O.D. iron pipe with a 2" dia. iron cap protrudes 9" above ground, bears N.68½°W., 22.4 ft. (rec. N.67°W., 22.4 ft.) 1974 DCS0.
New - 6" dia. W.Oak double blazed and scribed "¼ S36 CS BT" bears S.37°E., 19.3 ft.
Note - Corner located under high power lines at 4-way fence corner.

Fd. Ok by K. DeGroot, 2/2007 - 2007-0050

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 4/17/2008 - C.S. File 67/25-41

Fd. BC & 3 live BTs & 1¼" IP w/cap.