

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. to Secs. 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original - Elder &amp; Gile, Contract #31 dated April, 1853 ----- Set ¼ Sec. post, from which     A W.Oak 24" dia. bears N.16½°E., 240 lks. dist.     A W.Oak 12" dia. bears N.26½°W., 300 lks. dist.</p>
<p>Doug. Co. Surveyors - John M. Powell; Frank Jones; Joe Brady March, 1966 - C.S. 53/38-26 ----- Found - Orig. 24" W.Oak, now 48", N.16½°E., 159.1 ft.,           opened for scribing "BT".           No trace of other tree. Set - Brass cap at ¼ cor. mkd. County Surveyors Office       T27S R5W ¼ S 11 S 12 1966 New BTs - 12" W.Oak N.4°E., 143.8 ft. scribed ¼ S12 CS BT.           9" W.Oak N.77°W., 88.6 ft. scribed ¼ S11 CS BT. This corner lies about 160 ft. from top of hill on the south slope &amp; 2.6 ft. east of N-S fence line.</p>
<p>Doug. Co. Surveyors - Randall Smith; Stephen Flause - June 21, 1994 - C.S. 64/52-19 ----- Found - 2½" Brass cap on a 1½" O.D. I.P., protruding 15"           above ground (1966).           24" now 44" dia, W. Oak w/a previously opened blaze,           no scribing or blazes visible, bears N.16½°E.           159.1' OBT.           9" now 11" dia, W.Oak w/a fully healed double blaze,           bears N.79½°W. 88' 1966.           12" now 16" dia, W. Oak w/a fully healed "¼ S11 CS BT" bears N.69½°W. 241.2'.</p>
<p>Fd. Ok by K.DeGroot, 7/2005 - M146-23 Fd. BC &amp; BTs of record 7/2015 N. Hibbs, M169-58</p>
<p> </p>