

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 1, 2, 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post for Cor to Secs. 1, 2, 11 and 12, from which
A Laurel, 12" dia. bears N.87°E., 59 lks. dist.
A Fir, 18" dia. bears S.61°E., 16 lks. dist.
A Laurel, 12" dia. bears S.53°W., 55 lks. dist.
A Laurel, 10" dia. bears N.50°W., 55 lks. dist.

Glenn S. Baughman - For; 4 Star Land Development Co.
Dec. 30, 1967 (filed March 18, 1968) M 35 - 54

Set - Brass cap stamped Sec. Cor. Sec. 1, 2, 11 & 12.
Scribed - 4" Madrona bears S.89°E., 21.6 ft. scribed Sec.
12, T27S R5W.
Set - 1" I.R. bears S.62°W., 55.0 ft.
1" I.R. bears N.54°E., 16.0 ft.
1" I.R. bears N.62°W., 44.0 ft.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flauser;
May 17, 1994 - C.S. File 64/51-12

Monuments Found -

2½" Brass cap on a 1½" O.D. iron pipe protruding 22"
above ground. 1968

Accessories Found -

1" I.R. protruding 2" above ground bears S.67°W., 52.6
ft. (rec. S.62°W., 55.0 ft.) 1968.

1" I.R. protruding 4" above ground, bears N.39°E., 15.6
ft. (rec. N.54°E., 16.0 ft.) 1968.

1" I.R. protruding 1" above ground bears N.59°W., 43.4
ft. (rec. N.62°W., 44.0 ft.)

Monuments Set -

BC/IP referenced & removed, BC/IP returned to referenced
position, now protrudes 4" above ground. Measured
36" long.

New- 11" dia. Madrone (dia. taken 2 ft. above ground) bark
scribed "T27S R5W S2 CS BT" bears N.21°W., 29.5 ft.

10" dia. Madrone double blazed and scribed "T27S R5W S11
CS BT" bears S.45½°W., 48.2 ft.

19" dia. D.Fir double blazed and scribed "T27S R5W S12 CS
BT" bears S.84°E., 65.8 ft.

Note - Corner lies on a steep north easterly slope.

Fd. Ok by K.DeGroot, 7/2005 - M146-23